



Feature:

- Front panel dust proof, water proof and explosion proof
- Multi Touch technology use Projected Capacitive, 5-Wire Resistive and SAW is Option
- Desktop, secure, stable and 90-degree adjustment Stand
- VGA&DVI Input Interface

TDS 01 serial Touch Screen Monitor has full-plastic shell and sleek form factor design, compact and elegant. Multi-Touch performance, brilliant high-definition graphics, wide viewing angles. Stable Stand can be folded and 90-degrees (up and down) of adjustment. Removable Stand is easy to be packed and transported. The Touch Display has been authorized by FCC, CE, RoHS and IP65 Agency

TDS-01 Serial Desktop Touch Monitor Specification

Model	TDS 1501	TDS 1701	TDS 1901
Display Size	15"	17"	19"
Enclosure color	Dark gray		
Touch Technology	Max 10 Points Projected Capacitive, 5-Wire Resistive and SAW is Option		
Aspect Ratio	4:3		
Display Colors	16.7million		
Brightness	LED panel:250nit, Projected Capacitive: 225nit		
Viewing Angle	(H) ±80° or 160°/ (V): ±70° or 140°		
Touch Interface	USB		
Input Video Format	VGA&DVI		
Touch Response Time	8msec	5msec	5msec
Contrast Ratio	500:1	1000:1	1000:1
Display Resolution	1024 X768 @60,75Hz	1280 X1024@60,75HZ	1280 X1024@60,75HZ
Monitor Dimensions	W: 15.7" (400mm) H: 12.6" (321mm) D: 2.7" (69mm)	W: 15.7" (400mm) H: 13" (330mm) D: 2.7" (69mm)	W: 17.2" (437mm) H: 14.4" (365mm) D: 2.7" (69mm)
Weight (Actual & Shipping)	A: 15.4lbs (7.0KG) S: 17.6lbs (8.0KG)	A: 17.6lbs (8.0KG) S: 19.8lbs (9.0KG)	A: 18.7lbs (8.5KG) S: 20.9lbs (9.5KG)
Shipping Box Dimensions	W: 18.1" (460mm) H: 16.5" (420mm) D: 10.1" (257mm)	W: 18.1" (460mm) H: 16.5" (420mm) D: 10.1" (257mm)	W: 19.7" (500mm) H: 17.1" (435mm) D: 10.2" (260mm)
Input Frequency	Horizontal: 30.00-60 kHz, Vertical: 55-75 Hz		
Power Consumption	12V/4A		
Power Supply	Monitor Input Voltage:100-240 VAC, 50/60 Hz		
Temperature	Operating: 0°C to 50°C , Storage: -20°C to 70°C		
Humidity	Operating: 20% to 80%; Storage: 10% to 90%		
MTBF	50,000 hours demonstrated		
Mounting Options	75 mm VESA Mount, threaded-through mounting holes, under stand		
Agency Approvals	FCC, CE, RoHS and IP65		
Warranty	3-Year		

Contact US

TDS Touch (US HECHUANG Technology LLC)
2080 Walsh Ave., Unit C-1
Santa Clara, CA 95050

Tel: 1-408-688-2658
Email: info@tdstouch.com
Web: www.ustdstouch.com

