



Feature:

- Front panel dust proof and explosion proof
- Multi Touch technology use Projected Capacitive, 5-Wire Resistive and SAW is Option
- Mounting vest 75X75, Stable, secure stand can be folded (90-degree adjustment)
- VGA&DVI Input Interface

TDS 02 serial Touch Screen monitor has right angle, slim-bezel design, compact and elegant. Single or multi-touch performance, can meet the needs of different users. Brilliant high-definition graphics, wide viewing angles. Stable Stand can be folded and 90-degrees of adjustment. Removable Stand is easy to be packed and transported. The Touch Display has been authorized by FCC, CE, RoHS and IP65 Agency.

TDS-02 Serial Desktop Touch Monitor Specification

Model	TDS 1502	TDS 1702
Display Size	15"	17"
Enclosure color	Dark gray	
Touch Technology	10 points Projected Capacitive, 5-Wire Resistive or SAW is Option	
Aspect Ratio	4:3	
Display Colors	16.7million	
Brightness	LED panel:250nit, Projected Capacitive: 225nit	
Viewing Angle	(H) ±80° or 160° / (V): ±70° or 140°	
Input Video Format	VGA&DVI	
Touch Interface	USB or RS232	
Contrast Ratio	500:1	1000:1
Touch Response Time	<8msec	<5msec
Display Resolution	1024 X768 @60,75Hz	1280 X1024@60,75HZ
Monitor Dimensions	W: 13.6" (346mm) H: 10.6" (270mm) D: 0.8" (20.3mm)	W: 15.3" (388mm) H: 12.6" (320mm) D: 0.8" (20.3mm)
Weight (Actual & Shipping)	A: 12.1lb (5.5KG) S: 15.4lb (7KG)	A: 14.3lb (6.5KG) S: 17.6lb (8KG)
Shipping Box Dimensions	W: 18.1" (460mm) H: 16.5" (420mm) D: 10.1" (257mm)	W: 17.7" (450mm) H: 14.6" (370mm) D: 5.9" (150mm)
Input Frequency	Horizontal: 30.00-60 kHz, Vertical: 55-75 Hz	
Power Consumption	12V/4A	
Power Supply	Monitor Input Voltage:100-240 VAC, 50/60 Hz	
Operating Temperature	Operating: 0°C to 50°C, Storage: -20°C to 70°C	
Humidity	Operating: 20% to 80%; Storage: 10% to 90%	
MTBF	50,000 hours demonstrated	
Mounting Options	75 mm VESA mount Threaded-through mounting holes, under stand	
Agency Approvals	FCC, CE, RoHS and IP65	
Warranty	3-Year	

Contact US

TDS Touch (US HECHUANG Technology LLC)
2080 Walsh Ave., Unit C-1
Santa Clara, CA 95050

Tel: 1-408-688-2658
Email: info@tdstouch.com
Web: www.ustdstouch.com