

Anti-Sunlight, No Blind Zone For Any Size



- ① IR Touch Screen Frame
- ② 3-5mm Tempered Glass
- ③ LED Screen/ Projection Screen

BIN Series Infrared Touch Frame Feature:

- Real 10 Points multi Touch technology, Smart Assembly, integrated controller
- 18.65 Frame width, 10mm Frame thickness, Aluminum alloy black frame
- Stable and no drift, work well under direct sunlight
- High Precision, Fast Response and writing smoothly
- Touch input method: Finger, Finger of gloved, Stylus
- Support OS: Windows 7/8/10, Linux, Android
- 1-year warranty

BIN Series Infrared Touch Frame Specification

Touch Screen

Touch Points	10 Points
Available Standard Size	19"/21.5"/23.6"/27"/32"/37"/40"/42"/43"/46"/47"/52"/55"/65"
Customized Size	19" ~ 100"
Reported Resolution	32767X32767
Housing Color	Black Aluminum Alloy
Touch Accuracy	±2mm (over 90% Area)
Response Time	<16ms
Touch Input Method	Finger, Finger of gloved hand, Opaque objects
Minimum Stylus Size	Diameter > 5mm
Output Form	Coordinate Value
Glass	No Glass
Power Supply Mode	USB
USB2.0 Connector Type	Plug of type A
Transfer Speed	12Mbps, Full Speed
Signal	+5V, D-, D+, GND
Supply Voltage	DC+5V ± 5%
Power Consumption	0.9 ~ 2.5 W, according to different size
How to Supply it	From USB PORT of PC or powered HUB
Temperature	Operating: 0° to 60°C, Storage: -25° to 85°C
Humidity	Operating: 0%-85%RH, Storage: 0%-95% No-Condensing
ESD Capability	Contact discharge voltage is 8KV, air discharge voltage is 15KV
Multi Touch	Win8 / Win7 / XP / Linux / Mac OS / Android
Driver Software	Not needed

Contact US

TDS Touch
US HECHUANG Technology
Unit C-1, 2080 Walsh Ave,
Santa Clara, CA 95050

Tel: 1-408-688-2658
Email: info@tdstouch.com
Web: www.ustdstouch.com