



1020C PCAP 10.1", 16:10

Desktop
Digital Signage
Touch AIO



Feature:

- ✚ 10 Points PCAP Touch
- ✚ Commercial Grade LED
- ✚ Speaker
- ✚ Support OS:
Windows/Linux/Android
- ✚ 1280X800 DPI
- ✚ Portrait and Landscape
- ✚ HDMI&VGA&USB
- ✚ 1-Year Warranty
- ✚ CCC, FCC, CE, RoSH

20C-Series Products overview:

Wide-Aspect Ratio	1020C	10.1"	16:10	1280X800 DPI
	1520C	15.6"	16:9	1920X1080 DPI
	1820C	18.5"		1366X768 DPI
	2120C	21.5"		1920X1080 DPI
	2420C	23.8"		1920X1080 DPI

Option:

- AG and AR coating
- Base

1020C Desktop and Digital Signage Touch AIO

Specifications	
Model	1020C
Color	Black
Diagonal	10.1"
Active Display Area	8.54"X5.33"/216.96mmX135.6mm
LCD Technology	a-Si TFT-LCD
Dimensions	10.03"X6.91"X1.25"/255mmX175.5mmX31.8mm
Native Resolution	1920X1200 DPI
Aspect Ratio	16:10
Number of Colors	262K
Number of Touches	10 points touch
Brightness	LED Panel: 350 nits; PCAP Touch: 315 nits
Response	12ms
Viewing Angle	Horizontal: 89° /89°; Vertical: 89° /89°
Contrast Ratio	800:1
Temperature	Operating: -10°C-60°C; Storage: -20°C-70°C
Humidity	Operating: 0%-90%; Storage: 10%-95%
Weight	Unpackaged:5lbs; Packaged:7lbs
Mounting Options	100X100mm
Warranty	1-years standard
MTBF	12,000 hours demonstrated
Agency Approvals	FCC; CE; RoHS; CCC
What's in the Box	HDMI&VGA&USB Cable; Power Supply; UL Power Adapter
Power	12V/5A

Optional Computer Modules

Solution	Android	Intel X86	Custom
Processor	RK3288, 3368	Intel Celeron	Intel i3, i5 and i7
RAM	2G	DDR3: 2G/4G/8G/16G	
Storage	8G	SSD: 32G/64G/128G/256G	
OS	Android 5.1	Win7/8/10, Linux, Android	
Power	110-240V AC 50/60Hz		

Ordering Information

Model	Part Number	Touch Technology	Touch Interface	Surface Treatment	Video Interface
1020C	TDS1020C	PCAP	USB	AF Coating	HDMI, VGA

To find out more about TDS information, please go to www.ustdstouch.com, or call the office.

North America

Tel +1 408 688 2658
 Fax +1 669 600 5580
 Rachel.wu@tdstouch.com

2080 Walsh Ave. Unit C1
 Santa Clara, CA 95050
 www.ustdstouch.com

