

1738H 5:4 PCAP

High Brightness Touchscreen



Features

- + Open frame flat design, metal material
- + IP55 level front panel waterproof
- + Industrial grade LCD, LED backlight
- + Resolution 1280X1024@60Hz
- + 1000nits brightness backlight
- + 10 point projection capacitive touchscreen
- + Cover plate anti riot and anti-glare coating
- + Bonded with UV-resistant optical glue
- + Sunlight adaptive adjustment module
- + Air-cooled circulation cooling method
- + Video interface: HDMI+VGA
- + Reserve side and back assembly holes
- + Support OS: Windows/Android/Linux
- + 2-years Warranty



Optional:

- No Touch
- Touch interface: RS232
- 700-1200nits
- Cooling fan set
- Video interface: Display Port
- All-In-One (Android/Windows)



TDS1738H High Brightness Open Frame Touchscreen Monitor	
Diagonal	17''(5:4)
Color	Black/Silver
Native Resolution	1280X1024 @60Hz
Active Display Area	337.92X270.34(mm)
Dimensions	385.2X317.2X52(mm)
Contrast Ratio	1000:1
Number of Colors	16.7M
Viewing Angle	Horizontal: 85° /80°; Vertical:85° /80°
Brightness	LCD : 1000nits; PCAP: 835 nits
Brightness adjustment mode	*The brighter the ambient light, the brighter the LCD screen *The darker the ambient light, the darker the LCD screen, and enter the power saving mode
Response	10ms
Touch Technology	PCAP- 10 点
Mode of touch	Fingers/silicone pen
Glass thickness	3mm, tempered, surface AG coating
Glass hardness	7H(Mohs)
Touch accuracy	≤2mm
Viewing Angle	USB 2.0
Video Interface	HDMI+VGA
Input Voltage	AC: 100-240 VAC,50/60 Hz
Power Supply	12V-19V8A(Power Jack : 2.1mmx5.5mm)
Waterproof	Front panel :Front frame touch screen sealed to bezel Back: dust hole(Option: no hole)
Explosion-proof	450 grams of steel ball height 1.2 meters vertical drop center point will not break
Cooling method	Cooling holes exchange external air flow
Temperature	Operating: 0°C-50°C; Storage:-20°C-80°C
Humidity	Operating: 20%-70%; Storage:10%-80%
Mounting Options	Back VESA two groups of holes: 75mm&100mm Each of the four sides has a set of fixing holes: 142mm
Weight(net)	4.5KG
Shipping Dimensions	520X400X135(mm)
Warranty	2- years
MTBF	50,000 hours
Agency Approvals	FCC; CE; ROHS
What's in the Box	1*HDMI Cable;1*USB Cable; 1*Power Cable