## **TDS1502L 16:9 PCAP**


## Light Bar Touch Monitor





## **Features**

- + Flat appearance design
- + Metal shell, ultra-thin shape
- + Commercial grade LCD, LED backlight
- + Resolution 1920X1080FHD@60Hz
- + 10 point projection capacitive touchscreen
- + There are colored light bars all around
- + COB light bar with soft and even lighting
- + Support remote control and serial port control methods
- + Various marquee modes, Colors and speed can be adjusted
- + Video interface: HDMI+VGA
- + Back VESA wall mounting hole
- + Supports Windows/Android/Linux
- + 2-year warranty



## **Optional**

- No Touch
- Video interface: Display Port
- All-in-one(Built in motherboard)
- Brightness:500-1000nits

TDS1502L Light bar Touch Monitor Specification	
Model	1502L
Color	Black
Size	15.6 inch
Aspect Ratio	16:9
Active Area	344.16×193.5 (mm)
Dimensions	397.4X250.1X48.22(mm)
Resolution	1920 X1080FHD @60Hz
Viewing Angle	85/85/85 (Typ.)(CR≥10)
Number of Colors	262K , 72% NTSC
Brightness	LCD panel: 300cd/m2,PCAP Touch: 275cd/m2
Contrast Ratio	800:1
Response Time	8ms
Touch technology	PCAP (Projected Capacitive) -10 touch
Touch precision	>2mm
Touch interface	USB 2.0
Light bar	Control mode: #1: Remote control(Standard) #2: RS232 ((Options:Provides serial control protocol) Note:You can only choose one of the two methods above. Electrical Parameters:
	Lighting angle: 180° Working voltage: 12V Service life of LED:50,000hours
Video interface	HDMI+VGA
Speaker	Two*2W internal speakers
Input voltage	AC:100-240 VAC, 50/60 Hz
Power Supply	built in power supply
Weight(Unpackage)	5.6KG
Shipping Dimensions	460X330X145(mm)
Temperature	Operating: 0 °C to 40°C; Storage: -20°C to 60°C
Humidity	Operating: 20% to 70%; Storage: 10% to 80%
Sealability	Touchscreen sealed to bezel
MTBF	30,000 hours
VESA Mounting	75 X 75(mm) , 100X100(mm)
Warranty	2-Year
Agency Approvals	FCC, CE, ROHS
Agency Approvals Support OS	FCC, CE, ROHS Windows/Linux\Android
<u> </u>	

